

## Usage Guideline

# DRAFT5auth.031.001.01\_ESMAUG\_National-Reporting\_1.0.0

## MiFIR - Transaction Data - Reporting

This document describes a usage guideline restricting the base message **MX DRAFT5auth.031.001.01**. You can also consult [this information online](#).

Published by ESMA and generated by [MyStandards](#).

21 March 2017

# Table of Contents

<b>Message Functionality</b> .....	3
<b>1 Restriction summary</b> .....	4
<b>2 Structure</b> .....	5
<b>3 Message Building Blocks</b> .....	6
<b>4 Message Components</b> .....	7
<b>5 Message Datatypes</b> .....	17
<b>Legal Notices</b> .....	22

## Message Functionality

### Overview

The FinancialInstrumentReportingStatusAdvice message is sent by the national competent authority to the reporting agent to provide a status advice for the correctness, issues or errors that arise from the submitted report.

### Outline

The MiFIR - Transaction Data - Reporting / DRAFT5auth.031.001.01\_ESMAUG\_NationalReporting\_1.0.0 message is composed of 2 building blocks

a. StatusAdvice

Status advice report.

b. SupplementaryData

Additional information that can not be captured in the structured fields and/or any other specific block.

# 1 Restriction summary

This Usage Guideline restricts the DRAFT5auth.031.001.01 message.

Restriction Type	See page
Removed elements	6, 10, 13, 15, 18, 18, 18, 19, 19, 19
Make mandatory	7, 7
Reduce Multiplicity	n.a.
Ignore	n.a.
Text rules	n.a.
Conditional rules	n.a.
Fixed values	n.a.
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	n.a.
Extensions	n.a.
Synonyms	n.a.

## 2 Structure

⊘ Removed - ◇ Ignored - ▲ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>FinancialInstrumentReportingStatusAdviceV01</i>	<FinInstrmRptgStsAdvc>		[1..1]		
	<b>StatusAdvice</b>	<StsAdvc>		[1..*]		6
	MessageReportIdentifier	<MsgRptldr>		[0..1]		8
	MessageStatus	<MsgSts>		[1..1]		9
	RecordStatus	<RcrdSts>		[0..*]		9
	SupplementaryData	<SplmtryData>		[0..*]	⊘	10
	<b>SupplementaryData</b>	<SplmtryData>		[0..*]	⊘	6
	PlaceAndName	<PlcAndNm>		[0..1]		15
	Envelope	<Envlp>		[1..1]		15

## 3 Message Building Blocks

**Note** The following chapter identifies the building blocks of the FinancialInstrumentReportingStatusAdviceV01 message definition.

### 3.1 StatusAdvice

*XML Tag:* StsAdvc

*Presence:* [1..\*]

*Definition:* Status advice report.

The **StsAdvc** block contains the following elements (see datatype "[MessageReportHeader3](#)" on page 8 for details)

🚫 Removed - ⬠ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageReportIdentifier	<MsgRptldr>		[0..1]		8
	MessageStatus	<MsgSts>		[1..1]		9
	RecordStatus	<RcrdSts>		[0..*]		9
	SupplementaryData	<SplmtryData>		[0..*]	🚫	10

### 3.2 SupplementaryData

*XML Tag:* SplmtryData

*Presence:* [0..\*]

*Definition:* Additional information that can not be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 15 for details)

🚫 Removed - ⬠ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		15
	Envelope	<Envlp>		[1..1]		15

#### Usage Guideline details

- This element(DRAFT5auth.031.001.01/SupplementaryData) is removed.

# 4 Message Components

**Note** The following chapter identifies the FinancialInstrumentReportingStatusAdviceV01 message components.

## 4.1 GenericValidationRuleIdentification1

*Definition:* Information for the identification of a validation rule.

🚫 Removed - ⬜ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		7
	Description	<Desc>		[0..1]	<b>M</b>	7
	SchemeName	<SchmeNm>		[0..1]		8
	Issuer	<Issr>		[0..1]		8

**Used in element(s)**

"ValidationRule" on page 14, "ValidationRule" on page 12

### 4.1.1 Identification

*XML Tag:* Id

*Presence:* [1..1]

*Definition:* Unique and unambiguous identification of a validation rule.

*Datatype:* "Max35Text" on page 20

### 4.1.2 Description

*XML Tag:* Desc

*Presence:* [0..1]

*Definition:* Further information on the validation rule as identified in the Identification.

*Datatype:* "Max350Text" on page 20

**Usage Guideline details**

- on DRAFT5auth.031.001.01/StatusAdvice/MessageStatus/ValidationRule/Description  
*This element is now mandatory, the minimum occurrence has been changed to : 1*
- on DRAFT5auth.031.001.01/StatusAdvice/RecordStatus/ValidationRule/Description  
*This element is now mandatory, the minimum occurrence has been changed to : 1*

### 4.1.3 SchemeName

*XML Tag:* SchmeNm

*Presence:* [0..1]

*Definition:* Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "ValidationRuleSchemeName1Choice" on page 15 for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or}	[1..1]		16
	Proprietary	<Prtry>	Or}	[1..1]		16

### 4.1.4 Issuer

*XML Tag:* Issr

*Presence:* [0..1]

*Definition:* Entity that assigns the identification.

*Datatype:* "Max35Text" on page 20

## 4.2 MessageReportHeader3

*Definition:* Provides details of many status advice reports where many received reports are reported at once.

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageReportIdentifier	<MsgRptldr>		[0..1]		8
	MessageStatus	<MsgSts>		[1..1]		9
	RecordStatus	<RcrdSts>		[0..*]		9
	SupplementaryData	<SplmtryData>		[0..*]		10

**Used in element(s)**

"StatusAdvice" on page 6

### 4.2.1 MessageReportIdentifier

*XML Tag:* MsgRptldr

*Presence:* [0..1]

*Definition:* Provide detail on previously received message reports that are being reported as part of this status advice.

Usage:

Within MiFIR, when required, this field will be populated with the BAH Business Message Identifier field. Where only a single message report header is used, this field is not used and relies solely on the BAH Business Message Identifier field.

Datatype: ["Max35Text" on page 20](#)

## 4.2.2 MessageStatus

XML Tag: MsgSts

Presence: [1..1]

Definition: Details the submitting message status of the whole report that has been received.

The **MsgSts** block contains the following elements (see datatype ["StatusAdviceReport2" on page 11](#) for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReportStatus	<RptSts>		[1..1]		12
	ValidationRule	<VldtnRule>		[0..*]		12
	ReferenceDate	<RefDt>		[0..1]		12
	Statistics	<Sttstcs>		[0..1]		13

## 4.2.3 RecordStatus

XML Tag: RcrdSts

Presence: [0..\*]

Definition: Provides per record status on the report that has been submitted.

Usage:

Within MiFIR, the same record can be reported multiple times where different elements of the record have an issue.

The **RcrdSts** block contains the following elements (see datatype ["StatusReportRecord2" on page 13](#) for details)

 Removed -  Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalRecordIdentification	<OrgnlRcrdId>		[1..1]		13
	Status	<Sts>		[1..1]		14
	ValidationRule	<VldtnRule>		[0..*]		14
	SupplementaryData	<SplmtryData>		[0..*]		14

## 4.2.4 SupplementaryData

*XML Tag:* SplmtryData

*Presence:* [0..\*]

*Definition:* Additional information that can not be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 15 for details)

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		15
	Envelope	<Envlp>		[1..1]		15

### Usage Guideline details

- This element(DRAFT5auth.031.001.01/StatusAdvice/SupplementaryData) is removed.

## 4.3 NumberOfTransactionsPerStatus6

*Definition:* Provides detailed information on the number of transactions that are reported with a specific transaction status.

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTxs>		[1..1]		10
	DetailedStatus	<DtldSts>		[1..1]		10

### Used in element(s)

"NumberOfRecordsPerStatus" on page 11

### 4.3.1 DetailedNumberOfTransactions

*XML Tag:* DtldNbOfTxs

*Presence:* [1..1]

*Definition:* Number of individual transactions contained in the message, detailed per status.

*Datatype:* "Max15NumericText" on page 20

### 4.3.2 DetailedStatus

*XML Tag:* DtldSts

*Presence:* [1..1]

*Definition:* Common transaction status for all individual transactions reported.

*Datatype:* ["FinancialInstrumentReportingStatus3Code"](#) on page 18

## 4.4 OriginalReportStatistics2

*Definition:* Statistical information on the processing of records included in the original report.

🚫 Removed - ✦ Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TotalNumberOfRecords	<TtlNbOfRcrds>		[1..1]		11
	NumberOfRecordsPerStatus	<NbOfRcrdsPerSts>		[1..*]		11

**Used in element(s)**

["Statistics"](#) on page 13

### 4.4.1 TotalNumberOfRecords

*XML Tag:* TtlNbOfRcrds

*Presence:* [1..1]

*Definition:* Total numbers of records included in the original file.

*Datatype:* ["Max15NumericText"](#) on page 20

### 4.4.2 NumberOfRecordsPerStatus

*XML Tag:* NbOfRcrdsPerSts

*Presence:* [1..\*]

*Definition:* Detailed information on the number of records for each records status.

The **NbOfRcrdsPerSts** block contains the following elements (see datatype ["NumberOfTransactionsPerStatus6"](#) on page 10 for details)

🚫 Removed - ✦ Ignored - ⚠️ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTxs>		[1..1]		10
	DetailedStatus	<DtldSts>		[1..1]		10

## 4.5 StatusAdviceReport2

*Definition:* Provides the report level status advice.

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReportStatus	<RptSts>		[1..1]		12
	ValidationRule	<VldtnRule>		[0..*]		12
	ReferenceDate	<RefDt>		[0..1]	🚫	12
	Statistics	<Sttstcs>		[0..1]		13

#### Used in element(s)

["MessageStatus" on page 9](#)

### 4.5.1 ReportStatus

*XML Tag:* RptSts

*Presence:* [1..1]

*Definition:* Provides the status for the full report.

*Datatype:* ["FinancialInstrumentReportingStatus1Code" on page 17](#)

### 4.5.2 ValidationRule

*XML Tag:* VldtnRule

*Presence:* [0..\*]

*Definition:* Provides the details of the rule which could not be validated.

The **VldtnRule** block contains the following elements (see datatype ["GenericValidationRuleIdentification1" on page 7](#) for details)

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		7
	Description	<Desc>		[0..1]	<b>M</b>	7
	SchemeName	<SchmeNm>		[0..1]		8
	Issuer	<Issr>		[0..1]		8

### 4.5.3 ReferenceDate

*XML Tag:* RefDt

*Presence:* [0..1]

*Definition:* Indicates the report reference date.

*Datatype:* ["ISODate" on page 19](#)

Usage Guideline details

- This element(DRAFT5auth.031.001.01/StatusAdvice/MessageStatus/ReferenceDate) is removed.

## 4.5.4 Statistics

XML Tag: Sttstcs

Presence: [0..1]

Definition: Statistical information on the results of the records processing.

The **Sttstcs** block contains the following elements (see datatype "[OriginalReportStatistics2](#)" on page 11 for details)

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TotalNumberOfRecords	<TtlNbOfRcrds>		[1..1]		11
	NumberOfRecordsPerStatus	<NbOfRcrdsPerSts>		[1..*]		11

## 4.6 StatusReportRecord2

Definition: Provides the per record status details.

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalRecordIdentification	<OrgnlRcrdId>		[1..1]		13
	Status	<Sts>		[1..1]		14
	ValidationRule	<VldtnRule>		[0..*]		14
	SupplementaryData	<SplmtryData>		[0..*]	🚫	14

Used in element(s)

"RecordStatus" on page 9

### 4.6.1 OriginalRecordIdentification

XML Tag: OrgnlRcrdId

Presence: [1..1]

Definition: Unique and unambiguous technical identification of the original data for which the status is provided.

Datatype: "[Max140Text](#)" on page 19

## 4.6.2 Status

*XML Tag:* Sts

*Presence:* [1..1]

*Definition:* Defines status of the reported transaction.

*Datatype:* "FinancialInstrumentReportingStatus3Code" on page 18

## 4.6.3 ValidationRule

*XML Tag:* VldtnRule

*Presence:* [0..\*]

*Definition:* Provides the details of the rule which could not be validated.

The **VldtnRule** block contains the following elements (see datatype "[GenericValidationRuleIdentification1](#)" on page 7 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		7
	Description	<Desc>		[0..1]	<b>M</b>	7
	SchemeName	<SchmeNm>		[0..1]		8
	Issuer	<Issr>		[0..1]		8

## 4.6.4 SupplementaryData

*XML Tag:* SplmtryData

*Presence:* [0..\*]

*Definition:* Additional information that can not be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 15 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		15
	Envelope	<Envlp>		[1..1]		15

## Usage Guideline details

- This element(DRAFT5auth.031.001.01/StatusAdvice/RecordStatus/SupplementaryData) is removed.

## 4.7 SupplementaryData1

*Definition:* Additional information that can not be captured in the structured fields and/or any other specific block.

🚫 Removed - ⬠ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		15
	Envelope	<Envlp>		[1..1]		15

### Rules

#### R1 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

### Used in element(s)

["SupplementaryData" on page 6](#), ["SupplementaryData" on page 14](#), ["SupplementaryData" on page 10](#)

### 4.7.1 PlaceAndName

*XML Tag:* PlcAndNm

*Presence:* [0..1]

*Definition:* Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

*Datatype:* ["Max350Text" on page 20](#)

### 4.7.2 Envelope

*XML Tag:* Envlp

*Presence:* [1..1]

*Definition:* Technical element wrapping the supplementary data.

## 4.8 ValidationRuleSchemeName1Choice

*Definition:* Identifies a name of the identification scheme.

🚫 Removed - ⬠ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		16
	Proprietary	<Prtry>	Or}	[1..1]		16

Used in element(s)

["SchemeName" on page 8](#)

## 4.8.1 Code

*XML Tag:* Cd

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a coded form as published in an external list.

*Datatype:* ["ExternalValidationRuleIdentification1Code" on page 17](#)

## 4.8.2 Proprietary

*XML Tag:* Prtry

*Presence:* [1..1]

*Definition:* Name of the identification scheme, in a free text form.

*Datatype:* ["Max35Text" on page 20](#)

## 5 Message Datatypes

**Note** The following chapter identifies the datatypes that are used in the FinancialInstrumentReportingStatusAdviceV01 message.

### 5.1 ExternalValidationRuleIdentification1Code

*Definition:* Specifies the external validation rule identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from [www.iso20022.org](http://www.iso20022.org).

*Type:* Code

#### Format

minLength	1
maxLength	4

#### Used in element(s)

"Code" on page 16

### 5.2 FinancialInstrumentReportingStatus1Code

*Definition:* Specifies the financial instrument reporting status per message.

*Type:* Code

Code	Name	Definition
ACPT	Accepted	Transaction or report has been accepted.
CRPT	CorruptedFile	File containing the report is corrupted.
INCF	IncorrectFilename	File containing the report has an incorrect filename.
PART	PartiallyAccepted	Report has been partially accepted. A number of transactions have been accepted, whereas another number of transactions have not yet been accepted.
RCVD	Received	Report has been received.
RJCT	Rejected	Transaction or report has been rejected.
RMDR	Reminder	Reminder of a non received report.
WARN	Warning	Transaction has been accepted with warnings.

**Used in element(s)**

["ReportStatus" on page 12](#)

**Restricts**

["StatisticalReportingStatusCode" on page 21](#)

## 5.3 FinancialInstrumentReportingStatus3Code

*Definition:* Specifies the financial instrument reporting status per submitted item where an issue has been identified.

*Type:* Code

Code	Name	Definition
ACPD	AcceptedAfterPending	<p>Transaction or report has been accepted, following a pending status.</p> <hr/> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(DRAFT5auth.031.001.01/StatusAdvice/MessageStatus/Statistics/NumberOfRecordsPerStatus/DetailedStatus/AcceptedAfterPending) is removed.</li> <li>• This code(DRAFT5auth.031.001.01/StatusAdvice/RecordStatus/Status/AcceptedAfterPending) is removed.</li> </ul>
ACPT	Accepted	Transaction or report has been accepted.
PDNG	Pending	Processing of transaction or report is pending.
RCVD	Received	Report has been received.
RJCT	Rejected	Transaction or report has been rejected.
RJPD	RejectedAfterPending	<p>Transaction or report has been rejected, following a pending status.</p> <hr/> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(DRAFT5auth.031.001.01/StatusAdvice/MessageStatus/Statistics/NumberOfRecordsPerStatus/DetailedS-</li> </ul>

Code	Name	Definition
		<p>tatus/RejectedAfterPending) is removed.</p> <ul style="list-style-type: none"> <li>• This code(DRAFT5auth.031.001.01/StatusAdvice/RecordStatus/Status/RejectedAfterPending) is removed.</li> </ul>
WARN	Warning	<p>Transaction has been accepted with warnings.</p> <p><b>Usage Guideline restrictions for this code</b></p> <ul style="list-style-type: none"> <li>• This code(DRAFT5auth.031.001.01/StatusAdvice/MessageStatus/Statistics/NumberOfRecordsPerStatus/DetailedStatus/Warning) is removed.</li> <li>• This code(DRAFT5auth.031.001.01/StatusAdvice/RecordStatus/Status/Warning) is removed.</li> </ul>

**Used in element(s)**

["DetailedStatus"](#) on page 10, ["Status"](#) on page 14

**Restricts**

["StatisticalReportingStatusCode"](#) on page 21

## 5.4 ISODate

*Definition:* A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

*Type:* Date

**Used in element(s)**

["ReferenceDate"](#) on page 12

## 5.5 Max140Text

*Definition:* Specifies a character string with a maximum length of 140 characters.

*Type:* Text

**Format**

minLength 1

maxLength 140

**Used in element(s)**

"OriginalRecordIdentification" on page 13

## 5.6 Max15NumericText

*Definition:* Specifies a numeric string with a maximum length of 15 digits.

*Type:* Text

**Format**

pattern [0-9]{1,15}

**Used in element(s)**

"DetailedNumberOfTransactions" on page 10, "TotalNumberOfRecords" on page 11

## 5.7 Max350Text

*Definition:* Specifies a character string with a maximum length of 350 characters.

*Type:* Text

**Format**

minLength 1  
maxLength 350

**Used in element(s)**

"Description" on page 7, "PlaceAndName" on page 15

## 5.8 Max35Text

*Definition:* Specifies a character string with a maximum length of 35 characters.

*Type:* Text

**Format**

minLength 1  
maxLength 35

**Used in element(s)**

"Identification" on page 7, "Issuer" on page 8, "MessageReportIdentifier" on page 8, "Proprietary" on page 16

## 5.9 StatisticalReportingStatusCode

*Definition:* Specifies the status of a single statistical reporting transaction or of a group of statistical reporting transactions.

*Type:* Code

Code	Name	Definition
ACPD	AcceptedAfterPending	Transaction or report has been accepted, following a pending status.
ACPT	Accepted	Transaction or report has been accepted.
ACTC	AcceptedTechnicalValidation	Transaction or report has passed syntactical and semantical validation.
CRPT	CorruptedFile	File containing the report is corrupted.
INCF	IncorrectFilename	File containing the report has an incorrect filename.
PART	PartiallyAccepted	Report has been partially accepted. A number of transactions have been accepted, whereas another number of transactions have not yet been accepted.
PDNG	Pending	Processing of transaction or report is pending.
RCVD	Received	Report has been received.
RJCT	Rejected	Transaction or report has been rejected.
RJPD	RejectedAfterPending	Transaction or report has been rejected, following a pending status.
RMDR	Reminder	Reminder of a non received report.
WARN	Warning	Transaction has been accepted with warnings.

### Is restricted by

["FinancialInstrumentReportingStatus1Code"](#) on page 17,  
["FinancialInstrumentReportingStatus3Code"](#) on page 18

## Legal Notices

### Copyright

SWIFT © 2017. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

### Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

### Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.