

Usage Guideline

DRAFT4auth.031.001.01_ESMAUG_FDBTR-A_1.0.0

MiFIR - Transaction Data Reporting - TREM

This document describes a usage guideline restricting the base message **MX DRAFT4auth.031.001.01**. You can also consult [this information online](#).

Published by ESMA and generated by [MyStandards](#).

29 September 2016

Table of Contents

| | |
|---|-----------|
| Message Functionality | 3 |
| 1 Restriction summary | 4 |
| 2 Structure | 5 |
| 3 Message Building Blocks | 6 |
| 4 Message Components | 7 |
| 5 Message Datatypes | 17 |
| Legal Notices | 24 |

Message Functionality

Overview

The FinancialInstrumentReportingStatusAdvice message is sent by the national competent authority to the reporting agent to provide a status advice for the correctness, issues or errors that arise from the submitted report.

Outline

The MiFIR - Transaction Data Reporting - TREM / DRAFT4auth.031.001.01_ESMAUG_FDBTRA_1.0.0 message is composed of 2 building blocks

a. StatusAdvice

Status advice report.

b. SupplementaryData

Additional information that can not be captured in the structured fields and/or any other specific block.



1 Restriction summary

This Usage Guideline restricts the DRAFT4auth.031.001.01 message.

| Restriction Type | See page |
|---------------------|---|
| Removed elements | 6, 8, 8, 8, 8, 10, 13, 15, 17, 18, 18, 18, 19, 19, 19, 20, 20, 20, 20, 21 |
| Make mandatory | 7, 7 |
| Reduce Multiplicity | n.a. |
| Ignore | n.a. |
| Text rules | n.a. |
| Conditional rules | n.a. |
| Fixed values | n.a. |
| Comments | n.a. |
| Annotations | n.a. |
| Changed datatypes | n.a. |
| Extensions | n.a. |
| Synonyms | n.a. |

2 Structure

 Removed -
  Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--|------------------------------------|----|--------|---|------|
| | <i>FinancialInstrumentReportingStatusAdviceV01</i> | <i><FinInstrmRptgStsAdv></i> | | [1..1] | | |
| | StatusAdvice | <i><StsAdv></i> | | [1..*] | | 6 |
| | MessageReportIdentifier | <i><MsgRptIdr></i> | | [0..1] | | 9 |
| | MessageStatus | <i><MsgSts></i> | | [1..1] | | 9 |
| | RecordStatus | <i><RcrdSts></i> | | [0..*] | | 10 |
| | SupplementaryData | <i><SplmtryData></i> | | [0..*] |  | 10 |
| | SupplementaryData | <i><SplmtryData></i> | | [0..*] |  | 6 |
| | PlaceAndName | <i><PlcAndNm></i> | | [0..1] | | 15 |
| | Envelope | <i><Envlp></i> | | [1..1] | | 16 |

3 Message Building Blocks

Note The following chapter identifies the building blocks of the FinancialInstrumentReportingStatusAdviceV01 message definition.

3.1 StatusAdvice

XML Tag: StsAdv

Presence: [1..*]

Definition: Status advice report.

The **StsAdv** block contains the following elements (see datatype "[MessageReportHeader2](#)" on page 8 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|-------------------------|---------------|----|--------|------------------|------|
| | MessageReportIdentifier | <MsgRptIdr> | | [0..1] | | 9 |
| | MessageStatus | <MsgSts> | | [1..1] | | 9 |
| | RecordStatus | <RcrdSts> | | [0..*] | | 10 |
| | SupplementaryData | <SplmtryData> | | [0..*] | 🚫 | 10 |

3.2 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 15 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------|------------|----|--------|------------------|------|
| | PlaceAndName | <PlcAndNm> | | [0..1] | | 15 |
| | Envelope | <Envlp> | | [1..1] | | 16 |

Usage Guideline details

- This element(DRAFT4auth.031.001.01/SupplementaryData) is removed.

4 Message Components

Note The following chapter identifies the FinancialInstrumentReportingStatusAdviceV01 message components.

4.1 GenericValidationRuleIdentification1

Definition: Information for the identification of a validation rule.

⊘ Removed - ♦ Ignored - ▲ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
| | Identification | <Id> | | [1..1] | | 7 |
| | Description | <Desc> | | [0..1] | M | 7 |
| | SchemeName | <SchmeNm> | | [0..1] | ⊘ | 8 |
| | Issuer | <Issr> | | [0..1] | ⊘ | 8 |

Used in element(s)

"ValidationRule" on page 12, "ValidationRule" on page 14

4.1.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a validation rule.

Datatype: "Max35Text" on page 22

4.1.2 Description

XML Tag: Desc

Presence: [0..1]

Definition: Further information on the validation rule as identified in the Identification.

Datatype: "Max350Text" on page 22

Usage Guideline details

- on DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ValidationRule/Description
This element is now mandatory, the minimum occurrence has been changed to : 1
- on DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/ValidationRule/Description
This element is now mandatory, the minimum occurrence has been changed to : 1

4.1.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "ValidationRuleSchemeName1Choice" on page 16 for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| | Code | <Cd> | {Or | [1..1] | | 16 |
| | Proprietary | <Prtry> | Or} | [1..1] | | 16 |

Usage Guideline details

- This element(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/ValidationRule/SchemeName) is removed.
- This element(DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ValidationRule/SchemeName) is removed.

4.1.4 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 22

Usage Guideline details

- This element(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/ValidationRule/Issuer) is removed.
- This element(DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ValidationRule/Issuer) is removed.

4.2 MessageReportHeader2

Definition: Provides details of many status advice reports where many received reports are reported at once.

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|-------------------------|---------------|----|--------|------------------|------|
| | MessageReportIdentifier | <MsgRptIdr> | | [0..1] | | 9 |
| | MessageStatus | <MsgSts> | | [1..1] | | 9 |
| | RecordStatus | <RcrdSts> | | [0..*] | | 10 |
| | SupplementaryData | <SplmtryData> | | [0..*] | 🚫 | 10 |

Used in element(s)

"StatusAdvice" on page 6

4.2.1 MessageReportIdentifier

XML Tag: MsgRptIdr

Presence: [0..1]

Definition: Provide detail on previously received message reports that are being reported as part of this status advice.

Usage:

Within MiFIR, when required, this field will be populated with the BAH Business Message Identifier field. Where only a single message report header is used, this field is not used and relies solely on the BAH Business Message Identifier field.

Datatype: "Max35Text" on page 22

4.2.2 MessageStatus

XML Tag: MsgSts

Presence: [1..1]

Definition: Details the submitting message status of the whole report that has been received.

The **MsgSts** block contains the following elements (see datatype "StatusAdviceReport1" on page 12 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - M Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|----------------|-------------|----|--------|------------------|------|
| | ReportStatus | <RptSts> | | [1..1] | | 12 |
| | ValidationRule | <VldtnRule> | | [0..*] | | 12 |
| | ReferenceDate | <RefDt> | | [0..1] | 🚫 | 13 |
| | Statistics | <Sttstcs> | | [0..1] | | 13 |

4.2.3 RecordStatus

XML Tag: RcrdSts

Presence: [0..*]

Definition: Provides per record status on the report that has been submitted.

Usage:

Within MiFIR, the same record can be reported multiple times where different elements of the record have an issue.

The **RcrdSts** block contains the following elements (see datatype "[StatusReportRecord2](#)" on [page 13](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|------------------------------|---------------|----|--------|------------------|------|
| | OriginalRecordIdentification | <OrgnlRcrdId> | | [1..1] | | 14 |
| | Status | <Sts> | | [1..1] | | 14 |
| | ValidationRule | <VldtnRule> | | [0..*] | | 14 |
| | SupplementaryData | <SplmtryData> | | [0..*] | 🚫 | 15 |

4.2.4 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on [page 15](#) for details)

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------|------------|----|--------|------------------|------|
| | PlaceAndName | <PlcAndNm> | | [0..1] | | 15 |
| | Envelope | <Envlp> | | [1..1] | | 16 |

Usage Guideline details

- This element(DRAFT4auth.031.001.01/StatusAdvice/SupplementaryData) is removed.

4.3 NumberOfTransactionsPerStatus4

Definition: Provides detailed information on the number of transactions that are reported with a specific transaction status.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|------------------------------|---------------|----|--------|------------------|------|
| | DetailedNumberOfTransactions | <DtldNbOfTxs> | | [1..1] | | 11 |
| | DetailedStatus | <DtldSts> | | [1..1] | | 11 |

Used in element(s)

"NumberOfRecordsPerStatus" on page 12

4.3.1 DetailedNumberOfTransactions

XML Tag: DtldNbOfTxs

Presence: [1..1]

Definition: Number of individual transactions contained in the message, detailed per status.

Datatype: "Max15NumericText" on page 21

4.3.2 DetailedStatus

XML Tag: DtldSts

Presence: [1..1]

Definition: Common transaction status for all individual transactions reported.

Datatype: "FinancialInstrumentReportingStatus2Code" on page 18

4.4 OriginalReportStatistics1

Definition: Statistical information on the processing of records included in the original report.

🚫 Removed - 💡 Ignored - ⚠️ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------------------|-------------------|----|--------|------------------|------|
| | TotalNumberOfRecords | <TtlNbOfRcrds> | | [1..1] | | 11 |
| | NumberOfRecordsPerStatus | <NbOfRcrdsPerSts> | | [1..*] | | 12 |

Used in element(s)

"Statistics" on page 13

4.4.1 TotalNumberOfRecords

XML Tag: TtlNbOfRcrds

Presence: [1..1]

Definition: Total numbers of records included in the original file.

Datatype: "Max15NumericText" on page 21

4.4.2 NumberOfRecordsPerStatus

XML Tag: NbOfRcrdsPerSts

Presence: [1..*]

Definition: Detailed information on the number of records for each records status.

The **NbOfRcrdsPerSts** block contains the following elements (see datatype "[NumberOfTransactionsPerStatus4](#)" on page 10 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|------------------------------|--------------|----|--------|------------------|------|
| | DetailedNumberOfTransactions | <DtldNbOfTx> | | [1..1] | | 11 |
| | DetailedStatus | <DtldSts> | | [1..1] | | 11 |

4.5 StatusAdviceReport1

Definition: Provides the report level status advice.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|----------------|-------------|----|--------|------------------|------|
| | ReportStatus | <RptSts> | | [1..1] | | 12 |
| | ValidationRule | <VldtnRule> | | [0..*] | | 12 |
| | ReferenceDate | <RefDt> | | [0..1] | 🚫 | 13 |
| | Statistics | <Sttstcs> | | [0..1] | | 13 |

Used in element(s)

"[MessageStatus](#)" on page 9

4.5.1 ReportStatus

XML Tag: RptSts

Presence: [1..1]

Definition: Provides the status for the full report.

Datatype: "[FinancialInstrumentReportingStatus1Code](#)" on page 17

4.5.2 ValidationRule

XML Tag: VldtnRule

Presence: [0..*]

Definition: Provides the details of the rule which could not be validated.

The **ValidnRule** block contains the following elements (see datatype "[GenericValidationRuleIdentification1](#)" on page 7 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
| | Identification | <Id> | | [1..1] | | 7 |
| | Description | <Desc> | | [0..1] | M | 7 |
| | SchemeName | <SchmeNm> | | [0..1] | 🚫 | 8 |
| | Issuer | <Issr> | | [0..1] | 🚫 | 8 |

4.5.3 ReferenceDate

XML Tag: RefDt

Presence: [0..1]

Definition: Indicates the report reference date.

Datatype: "[ISODate](#)" on page 21

Usage Guideline details

- This element([DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ReferenceDate](#)) is removed.

4.5.4 Statistics

XML Tag: Sttstcs

Presence: [0..1]

Definition: Statistical information on the results of the records processing.

The **Sttstcs** block contains the following elements (see datatype "[OriginalReportStatistics1](#)" on page 11 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------------------|-------------------|----|--------|------------------|------|
| | TotalNumberOfRecords | <TtlNbOfRcrds> | | [1..1] | | 11 |
| | NumberOfRecordsPerStatus | <NbOfRcrdsPerSts> | | [1..*] | | 12 |

4.6 StatusReportRecord2

Definition: Provides the per record status details.

🚫 Removed - ♦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|------------------------------|---------------|----|--------|------------------|------|
| | OriginalRecordIdentification | <OrgnlRcrdId> | | [1..1] | | 14 |
| | Status | <Sts> | | [1..1] | | 14 |
| | ValidationRule | <VldtnRule> | | [0..*] | | 14 |
| | SupplementaryData | <SplmtryData> | | [0..*] | 🚫 | 15 |

Used in element(s)

"RecordStatus" on page 10

4.6.1 OriginalRecordIdentification

XML Tag: OrgnlRcrdId

Presence: [1..1]

Definition: Unique and unambiguous technical identification of the original data for which the status is provided.

Datatype: "Max140Text" on page 21

4.6.2 Status

XML Tag: Sts

Presence: [1..1]

Definition: Defines status of the reported transaction.

Datatype: "FinancialInstrumentReportingStatus3Code" on page 20

4.6.3 ValidationRule

XML Tag: VldtnRule

Presence: [0..*]

Definition: Provides the details of the rule which could not be validated.

The **VldtnRule** block contains the following elements (see datatype "GenericValidationRuleIdentification1" on page 7 for details)

🚫 Removed - ♦ Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|----------------|-----------|----|--------|------------------|------|
| | Identification | <Id> | | [1..1] | | 7 |
| | Description | <Desc> | | [0..1] | M | 7 |
| | SchemeName | <SchmeNm> | | [0..1] | 🚫 | 8 |
| | Issuer | <Issr> | | [0..1] | 🚫 | 8 |

4.6.4 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "[SupplementaryData1](#)" on page 15 for details)

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------|------------|----|--------|------------------|------|
| | PlaceAndName | <PlcAndNm> | | [0..1] | | 15 |
| | Envelope | <Envlp> | | [1..1] | | 16 |

Usage Guideline details

- This element(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/SupplementaryData) is removed.

4.7 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

🚫 Removed - 💡 Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------|------------|----|--------|------------------|------|
| | PlaceAndName | <PlcAndNm> | | [0..1] | | 15 |
| | Envelope | <Envlp> | | [1..1] | | 16 |

Rules

R1 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"[SupplementaryData](#)" on page 6, "[SupplementaryData](#)" on page 10, "[SupplementaryData](#)" on page 15

4.7.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 22

4.7.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

4.8 ValidationRuleSchemeName1Choice

Definition: Identifies a name of the identification scheme.

🚫 Removed - 💡 Ignored - ⚠️ Details below - 📌 Mandatory - R[x..x] Repeatability[details]

| Index | Message Item | <XML Tag> | Or | Mult. | Usage Guidelines | Page |
|-------|--------------|-----------|-----|--------|------------------|------|
| | Code | <Cd> | {Or | [1..1] | | 16 |
| | Proprietary | <Prtry> | Or} | [1..1] | | 16 |

Used in element(s)

"SchemeName" on page 8

4.8.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalValidationRuleIdentification1Code" on page 17

4.8.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 22

5 Message Datatypes

Note The following chapter identifies the datatypes that are used in the FinancialInstrumentReportingStatusAdviceV01 message.

5.1 ExternalValidationRuleIdentification1Code

Definition: Specifies the external validation rule identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: Code

Format

| | |
|-----------|---|
| minLength | 1 |
| maxLength | 4 |

Used in element(s)

"Code" on page 16

5.2 FinancialInstrumentReportingStatus1Code

Definition: Specifies the financial instrument reporting status per message.

Type: Code

| Code | Name | Definition |
|------|-------------------|--|
| ACPT | Accepted | Transaction or report has been accepted. |
| CRPT | CorruptedFile | File containing the report is corrupted. |
| INCF | IncorrectFilename | File containing the report has an incorrect filename. <div> Usage Guideline restrictions for this code <ul style="list-style-type: none"> This code(DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ReportStatus/IncorrectFilename) is removed. </div> |
| PART | PartiallyAccepted | Report has been partially accepted. A number of transactions have been accepted, whereas another number of transactions have not yet been accepted. |

| Code | Name | Definition |
|------|----------|---|
| RCVD | Received | Report has been received. Usage Guideline restrictions for this code <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ReportStatus/Received) is removed. |
| RJCT | Rejected | Transaction or report has been rejected. |
| RMDR | Reminder | Reminder of a non received report. |
| WARN | Warning | Transaction has been accepted with warnings. Usage Guideline restrictions for this code <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/ReportStatus/Warning) is removed. |

Used in element(s)

"ReportStatus" on page 12

Restricts

"StatisticalReportingStatusCode" on page 22

5.3 FinancialInstrumentReportingStatus2Code

Definition: Specifies the financial instrument reporting status per submitted item where an issue has been identified.

Type: Code

| Code | Name | Definition |
|------|----------------------|--|
| ACPD | AcceptedAfterPending | Transaction or report has been accepted, following a pending status. Usage Guideline restrictions for this code <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/MessageStatus/Statistics/NumberOfRecordsPerStatus/DetailedS- |

| Code | Name | Definition |
|------|----------------------|---|
| | | tatus/AcceptedAfterPending) is removed. |
| ACPT | Accepted | Transaction or report has been accepted. |
| PDNG | Pending | <p>Processing of transaction or report is pending.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/MessageS-tatus/Statistics/Num-berOfRecordsPerStatus/DetailedS-tatus/Pending) is removed. |
| RJCT | Rejected | Transaction or report has been rejected. |
| RJPD | RejectedAfterPending | <p>Transaction or report has been rejected, following a pending status.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/MessageS-tatus/Statistics/Num-berOfRecordsPerStatus/DetailedS-tatus/RejectedAfterPending) is removed. |
| WARN | Warning | <p>Transaction has been accepted with warnings.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/MessageS-tatus/Statistics/Num-berOfRecordsPerStatus/DetailedS-tatus/Warning) is removed. |

Used in element(s)

"DetailedStatus" on page 11

Restricts

"StatisticalReportingStatusCode" on page 22

5.4 FinancialInstrumentReportingStatus3Code

Definition: Specifies the financial instrument reporting status per submitted item where an issue has been identified.

Type: Code

| Code | Name | Definition |
|------|----------------------|---|
| ACPD | AcceptedAfterPending | <p>Transaction or report has been accepted, following a pending status.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/Status/AcceptedAfterPending) is removed. |
| ACPT | Accepted | Transaction or report has been accepted. |
| PDNG | Pending | <p>Processing of transaction or report is pending.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/Status/Pending) is removed. |
| RCVD | Received | <p>Report has been received.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/Status/Received) is removed. |
| RJCT | Rejected | Transaction or report has been rejected. |
| RJPD | RejectedAfterPending | <p>Transaction or report has been rejected, following a pending status.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/Status/RejectedAfterPending) is removed. |

| Code | Name | Definition |
|------|---------|--|
| | | tus/RejectedAfterPending) is removed. |
| WARN | Warning | <p>Transaction has been accepted with warnings.</p> <p>Usage Guideline restrictions for this code</p> <ul style="list-style-type: none"> • This code(DRAFT4auth.031.001.01/StatusAdvice/RecordStatus/Status/Warning) is removed. |

Used in element(s)

"Status" on page 14

Restricts

"StatisticalReportingStatusCode" on page 22

5.5 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"ReferenceDate" on page 13

5.6 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

| | |
|-----------|-----|
| minLength | 1 |
| maxLength | 140 |

Used in element(s)

"OriginalRecordIdentification" on page 14

5.7 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern [0-9]{1,15}

Used in element(s)

"DetailedNumberOfTransactions" on page 11, "TotalNumberOfRecords" on page 11

5.8 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

minLength 1
maxLength 350

Used in element(s)

"Description" on page 7, "PlaceAndName" on page 15

5.9 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

minLength 1
maxLength 35

Used in element(s)

"Identification" on page 7, "Issuer" on page 8, "MessageReportIdentifier" on page 9, "Proprietary" on page 16

5.10 StatisticalReportingStatusCode

Definition: Specifies the status of a single statistical reporting transaction or of a group of statistical reporting transactions.

Type: Code

| Code | Name | Definition |
|------|----------------------|--|
| ACPD | AcceptedAfterPending | Transaction or report has been accepted, following a pending status. |
| ACPT | Accepted | Transaction or report has been accepted. |

| Code | Name | Definition |
|------|-----------------------------|---|
| ACTC | AcceptedTechnicalValidation | Transaction or report has passed syntactical and semantical validation. |
| CRPT | CorruptedFile | File containing the report is corrupted. |
| INCF | IncorrectFilename | File containing the report has an incorrect filename. |
| PART | PartiallyAccepted | Report has been partially accepted. A number of transactions have been accepted, whereas another number of transactions have not yet been accepted. |
| PDNG | Pending | Processing of transaction or report is pending. |
| RCVD | Received | Report has been received. |
| RJCT | Rejected | Transaction or report has been rejected. |
| RJPD | RejectedAfterPending | Transaction or report has been rejected, following a pending status. |
| RMDR | Reminder | Reminder of a non received report. |
| WARN | Warning | Transaction has been accepted with warnings. |

Is restricted by

"FinancialInstrumentReportingStatus1Code" on page 17,

"FinancialInstrumentReportingStatus2Code" on page 18,

"FinancialInstrumentReportingStatus3Code" on page 20

Legal Notices

Copyright

SWIFT © 2016. All rights reserved.

This material is a component of MyStandards, the SWIFT collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with SWIFT SCRL, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain SWIFT or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. SWIFT does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of SWIFT or its licensors.

Trademarks and Patents

SWIFT is the trade name of S.W.I.F.T. SCRL. The following are registered trademarks of SWIFT: SWIFT, the SWIFT logo, 3SKey, Innotribe, Sibos, SWIFTNet, MyStandards, SWIFTReady, and Accord. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.